



GH Hydraulic swing
beam shears




pilses

adira
innovation works >>>



GH 0640

Model		GH 00420	GH 00630	GH 00640	GH 00660	GH 01030	GH 01040	GH 01330	GH 01340	GH 01360
Cutting Capacity										
Mild Steel (45daN/mm)	mm	4	6,5	6,5	6,5	10	10	13	13	13
Stainless Steel (70daN/mm ²)	mm	2,5	4	4	4	6,5	6,5	8	8	8
Cutting Length	mm	2050	3050	4050	6100	3050	4050	3050	4050	6120
Frame Gap	mm	260	260	260	260	260	260	260	260	260
Rake Angle	degrees	11/6	11/3	11/3	11/6	2	11/2	2	11/2	12/5
Blade Gap Adjustment	mm	0.05 - 0.6	0.05 - 1.1	0.05 - 1.1	0.05 - 1.2	0.05 - 1.6	0.05 - 1.6	0.05 - 2	0.05 - 2	0.05 - 2
Motor Power	kW	9	15	15	18	15	15	18	18	18
Number of Holddowns	-	9	13	19	25	16	22	16	22	31
Back Gauge Range	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000
Strokes/Minute	stroke/min	45	24	21	19	10	11	9	8	6
Dimensions (CE - configuration)										
Length	mm	2950	3950	4980	7120	3980	4980	3980	4980	7100
Width	mm	2480	2480	2480	2580	2820	2820	2820	2820	3100
Transportation Width	mm	2180	2180	2180	2280	2280	2280	2280	2280	2450
Height	mm	1730	1730	1825	2150	2150	2150	2150	2150	2400
Approx. Net Weight	kg	5000	5900	8100	15000	10000	13500	10000	13500	31000

All data are approximate. Specifications are subject to changes without notice. Shown specifications may vary from country to c

ountry. For different configurations consult your Adira specialist.



DC/MAP-C-163-I-15/02